

CLASSIC CONTEMPORARY SERIES SPEC SHEET

(Desks, Returns, and Credenzas)

Pedestals: Available in Box/File configuration. All pedestals standard with turn-key lock. **Pedestals are multi-formed one-piece jackets from 20 gauge CRS steel. Both front and rear 18 gauge vertical jacket upright stiffeners are multi formed for strength and welded to the sides**, and multi-slotted for suspension attachment and lock bar insertion at the factory or in the field. **The 20-gauge pedestal top frame cross piece multi-formed to make up the top section**, which encloses the pedestal, as well as houses the standard lock. Box drawers and file drawers operate on a **3 segment full progression suspension**, also includes ball race suspensions, precision rolled formed on hardened steel ball bearings. **Box drawer 1-piece construction having double wall front with welded fronts**, and are field replaceable. Slots on box drawer sides accept standard steel adjustable divider. Letter drawer bottom and side bodies are one piece multi-formed units. Letter drawers have full height sides offering full time front to back hanging folder filing. **Drawer fronts are 20 gauge with multi-formed full pull integral handle and are field replaceable.** Drawer backs are 22 gauge. **14-gauge vertical lock bar** is installed, operates and is shielded by the right front upright.

Work surfaces: Post formed waterfall edge, front and rear. Work surfaces are 1-1/8" thick 45#-48# density M3 commercial grade wood core provided with bottom protective balancing sheet. Overall thickness, including high-pressure laminate is 1-1/4" thick.

T-Edge, 3mm or self-edge are optional. Desk work surfaces available with rear center grommet. Desks, credenzas and returns are shipped assembled. Desk chassis is secured to top by mounting screw fasteners.

End-Panels: Flush slab end side panels are multi-formed for strength with inner walls spot-welded in place. **Two 16 gauge 1" square inner leg structural members (uprights) included in each end panel and welded to 1" square tubing cross-member ("H" structure) to provide structural integrity.** Two 1" adjustable non-corrosive leveling glides are on each end panel. **Inner and outer walls are 20 gauge.**

Modesty Panels: Available full height or ¾ height (8 5/8" from the floor). All modesty panels are 20-gauge cold rolled steel with multi formed flanges along each edge, including multi-formed double flanges formed on the bottom. Has cable channel 4-1/2"h x 1-1/8"d.

Optional Reference Shelves: Available with optional 18 gauge steel reference or pull-out shelves.

Optional Center drawers: Two 20 gauge center drawers available as options with or without locks, either 21"w x 15"d with 5 front compartments or 15"w x 15"d w/3 front compartments- built within a frame with ball bearing race suspensions.

Finish: All Invincible[™] steel products are processed through a 5-stage industrial washer to remove oil and organics from the surface while applying an iron phosphate conversion coating to promote adhesion and corrosion resistance as a pre-paint treatment. In addition, parts are rinsed with a non-chrome sealer to aid in paint adhesion and to further protect the metal. **The surface is then painted with environmentally-friendly and highly durable hybrid powder coat paint applied electro-statically and cured at high temperature.** Invincible[™] products are available in a full assortment of standard Invincible[™] colors, both smooth and textured finishes, as well as special order colors.