

# STORAGE CABINET SPECIFICATION SHEET

(Hinged Doors with locking turn handle)

Description: These units are premium storage cabinets with adjustable shelves, three point keyed locking turn handle, 6 way adjustable hinged doors and adjustable glides for leveling. Full flush bottom and top welded to the sides and back. Top has 1 7/16" flanges on three sides. Two full height uprights welded on each side (4) total along the front and back of the cabinet with adjustable shelf support clip holes in intervals of 1". Multi-formed steel shelf supported by (4) multi-formed plated shelf clips. Four adjustable glides accessible from inside the cabinet and supported by (4) 16-gauge multi-formed glide supports. It comes equipped with a double bit key lock (with 2 keys included) mounted on the right hand door.

| <u>Dimensions:</u>        | <u>Width</u>    | <u>Depth</u>                     | <u>Height</u> | <u>Shelves</u> |
|---------------------------|-----------------|----------------------------------|---------------|----------------|
|                           | 30" – 36" – 42" | 18 1/8"                          | 27 11/16"     | 1              |
|                           |                 |                                  | 39 13/16"     | 2              |
|                           |                 |                                  | 65 1/4"       | 4              |
| <b>Outer Frame Gauges</b> |                 | <b>Doors &amp; Shelf Gauges</b>  |               |                |
| Top & Bottom              | 18              | R.H. Door w/ lock                |               | 20             |
| Back & Side               | 20              | L.H. Door                        |               | 20             |
| <b>Inner Frame Gauges</b> |                 | Door Support (2)                 |               | 18             |
| Top Offset                | 22              | Shelves                          |               | 20             |
| Top Stiffener             | 20              |                                  |               |                |
| R.H. Upright              | 18              | <b>Lock &amp; Closure Gauges</b> |               |                |
| L.H. Upright              | 18              | Lock Bar (Inside case-2 ea.)     |               | 5/16" Rod      |
| Adjustable Shelf Strips   | 20              | Lock Bar Lever                   |               | 16             |
| Glide Support (4)         | 16              | Lock Bar Guide (2)               |               | 18             |

**Finish:** All Invincible<sup>™</sup> steel products are processed through a 5-stage industrial washer to remove oil and organics from the surface while applying an iron phosphate conversion coating to promote adhesion and corrosion resistance as a pre-paint treatment. In addition, parts are rinsed with a non-chrome sealer to aid in paint adhesion and to further protect the metal. **The surface is then painted with environmentally-friendly and highly durable hybrid powder coat paint applied electro-statically and cured at high temperature.** Invincible<sup>™</sup> products are available in a full assortment of standard Invincible<sup>™</sup> colors, both smooth and textured finishes, as well as special order colors.